


Standard Color Chart

Digital reference | Match and approve a physical sample before use.

				
Oyster T010 LRV 57	Rose T019 LRV 55	Beach T013 LRV 37	Ochre 10433 LRV 47	Rawhide T022 LRV 30
				
Tierra 272 LRV 31	Laredo 3020 LRV 17	Mission 3036 LRV 50	Naples 3009 LRV 52	Deerskin 1568 LRV 37
				
Buffalo 806 LRV 38	Agave 3041 LRV 17	Red Rock 3043 LRV 14	Mountain 3014 LRV 56	Plateau 3019 LRV 50
				
Waters Edge 3029 LRV 40	Marada 3022 LRV 17	Channel 3017 LRV 21	Sheridan 3034 LRV 13	Limestone 10402 LRV 55
				
Clear Linen 10431 LRV 64	Tumbleweed T014 LRV 37	Larkspur 3026 LRV 48	River Rock 1565 LRV 34	Saddle T015 LRV 29

COLOR SELECTION Screens and printers show approximate colors. Finish and texture affect appearance. Select and approve a physical sample made by the applicator with the project tools, methods and materials before application. Parex does not guarantee the color accuracy of applied finishes.

DARK COLORS / EIFS Sika advises against colors below LRV 20 on EIFS containing expanded polystyrene (EPS). Its chart cites an approximate sustained EPS temperature limit of 160°F (71°C); dark finishes may exceed it in some climates. Consult Parex Technical Services for project-specific suitability.

Standard Color Chart

Digital reference | Match and approve a physical sample before use.



Buckskin T020
LRV 45



Sonata 3005
LRV 64



Haven 3010
LRV 45



Winthrop 3008
LRV 40



Taos 1569
LRV 21



Clay 1571
LRV 24



Los Olivos 3040
LRV 15



Stone Bluff 351
LRV 45




Lonestar 3028
LRV 29



Sea Day 3018
LRV 33




Pewter 3016
LRV 29



Cavern 3031
LRV 17



Rose Cello 3030
LRV 17



Ivory 10444
LRV 66



Moonstone 10446
LRV 51



Almond 10407
LRV 58



Italia 3023
LRV 26



Pottery 1566
LRV 31



Cafe T016
LRV 24



Quarry 3035
LRV 49



Lariat 821
LRV 57



Resin 3025
LRV 41



Canyon 3007
LRV 28



Hacienda 3001
LRV 26






Rio Bravo 825
LRV 20

COLOR SELECTION Screens and printers show approximate colors. Finish and texture affect appearance. Select and approve a physical sample made by the applicator with the project tools, methods and materials before application. Parex does not guarantee the color accuracy of applied finishes.

DARK COLORS / EIFS Sika advises against colors below LRV 20 on EIFS containing expanded polystyrene (EPS). Its chart cites an approximate sustained EPS temperature limit of 160°F (71°C); dark finishes may exceed it in some climates. Consult Parex Technical Services for project-specific suitability.

Standard Color Chart

Digital reference | Match and approve a physical sample before use.

				
Snowball 10400 LRV 75	Ranch 3024 LRV 27	Canvas 3004 LRV 45	Dutch Blue 3042 LRV 23	Teal Med 3037 LRV 16
				
Basalt 3015 LRV 29	Cliff 3039 LRV 6	Light T017 LRV 57	Warm Sand 10432 LRV 43	Bamboo 10425 LRV 53
				
Dry River 817 LRV 34	Sombrero T023 LRV 23	Twig 3021 LRV 21	Moondance 3027 LRV 66	Tawny 3006 LRV 45
				
Casa 827 LRV 52	Montecito 3002 LRV 36	Sun Dried 3011 LRV 17	Vega 1570 LRV 23	Dove 3003 LRV 53
				
Gray White 3013 LRV 61	Santiago 3032 LRV 19	Sweet Grass 3012 LRV 39	Blue Med 3038 LRV 12	Tuxedo 3033 LRV 12

COLOR SELECTION Screens and printers show approximate colors. Finish and texture affect appearance. Select and approve a physical sample made by the applicator with the project tools, methods and materials before application. Parex does not guarantee the color accuracy of applied finishes.

DARK COLORS / EIFS Sika advises against colors below LRV 20 on EIFS containing expanded polystyrene (EPS). Its chart cites an approximate sustained EPS temperature limit of 160°F (71°C); dark finishes may exceed it in some climates. Consult Parex Technical Services for project-specific suitability.