








Standard Color Chart

Digital reference | Match and approve a physical sample before use.

				
3025 Paprika* LRV 28	543 Slate Rose LRV 51	3029 Creme Brule LRV 44	3059 Mosque LRV 49	3035 Strawberry* LRV 51
				
547 Blush LRV 68	3037 Mariposa LRV 67	3041 Firenze LRV 62	3053 Tawny LRV 63	600 Silverado LRV 59
				
3074 Coriander LRV 63	3047 Tortilla LRV 71	528 Sun Glow LRV 55	3080 Ecru LRV 78	3086 Lion's Mane LRV 65
				
3045 Edelweiss LRV 81	3081 Empire LRV 57	3068 Birch LRV 75	3076 Umber LRV 30	3050 Nougat LRV 78
				
3077 Ocha LRV 42	410 Snow LRV 73	3082 Cumin* LRV 47	3094 Harrier LRV 66	3078 Gold Ochre* LRV 48
				
3099 Brume LRV 58	3079 Bay Leaf* LRV 40	869 London Fog LRV 51	609 Greenbrier* LRV 30	755 Sea Mist* LRV 54
				
605 Bluet* LRV 23	3093 Seattle Mist* LRV 53			









COLOR SELECTION Screens and printers show approximate colors. Choose a physical sample made by the applicator with the project tools, methods and materials before final selection.

DARK COLORS / EIFS Sika advises against colors below LRV 20 on EIFS containing expanded polystyrene (EPS). Its chart cites an approximate sustained EPS temperature limit of 160°F (71°C); dark finishes may exceed it in some climates. Consult Senergy Technical Services for project-specific suitability.

ASTERISK (*) Starred colors use organic pigments with lower lightfastness and greater fading risk. Inform the owner, architect and builder.

Standard Color Chart

Digital reference | Match and approve a physical sample before use.

				
3026 Clay Pot LRV 47	614 Clay LRV 38	3031 Ground Mace LRV 48	3073 Hickory LRV 45	3030 Solitude LRV 64
				
612 Seashell LRV 47	3028 Vintage LRV 79	549 Pink Ash LRV 55	3038 Scarborough LRV 70	3103 Sandstorm LRV 54
				
3066 Bambi LRV 63	3063 Frappe LRV 75	3067 Egg Cream LRV 63	3062 Angora LRV 75	3089 Gauze LRV 85
				
3056 Papyrus LRV 52	3090 Honeysuckle LRV 82	342 Parchment LRV 58	440 Custard LRV 74	3100 Biscuit LRV 66
				
3085 Meringue LRV 77	425 Salt White LRV 58	3097 Saddlesoap LRV 65	3101 Vibrato LRV 53	3083 Flax* LRV 55
				
752 Dawn Grey LRV 45	3088 Cat's Eye* LRV 68	751 Morning Mist LRV 45	608 Glade* LRV 35	3109 Grey Ash* LRV 39
				
604 Truro Blue* LRV 46	758 Thunder Mist LRV 33			















COLOR SELECTION Screens and printers show approximate colors. Choose a physical sample made by the applicator with the project tools, methods and materials before final selection.

DARK COLORS / EIFS Sika advises against colors below LRV 20 on EIFS containing expanded polystyrene (EPS). Its chart cites an approximate sustained EPS temperature limit of 160°F (71°C); dark finishes may exceed it in some climates. Consult Senergy Technical Services for project-specific suitability.

ASTERISK (*) Starred colors use organic pigments with lower lightfastness and greater fading risk. Inform the owner, architect and builder.

Standard Color Chart

Digital reference | Match and approve a physical sample before use.

				
545 Dusty Peach LRV 56	620 Ash Brown LRV 29	3027 Mannequin LRV 77	618 Hazelnut LRV 33	3036 Daiquiri LRV 63
				
3052 Cardamom LRV 45	3033 Peacherine LRV 82	3064 Rawhide LRV 39	3039 Coral LRV 81	3060 Cafe Au Lait LRV 57
				
3049 Artisan LRV 73	3061 Dune LRV 73	3044 Ramie LRV 76	3055 Shearling LRV 70	3046 Finesse LRV 84
				
3040 Jute LRV 73	3084 Egg Nog LRV 83	431 Almond LRV 60	3075 Parsnip LRV 80	427 Oatmeal LRV 57
				
3034 Muslin LRV 77	610 Porridge LRV 48	601 Dynasty LRV 77	3098 Crescent LRV 63	3091 Sprite* LRV 79
				
3104 Walden LRV 42	3087 Mint Aspic* LRV 69	3102 Revere LRV 44	607 Gem* LRV 4	872 Whale Grey LRV 33
				
603 Atlantis* LRV 62	757 Magnum* LRV 34			













COLOR SELECTION Screens and printers show approximate colors. Choose a physical sample made by the applicator with the project tools, methods and materials before final selection.

DARK COLORS / EIFS Sika advises against colors below LRV 20 on EIFS containing expanded polystyrene (EPS). Its chart cites an approximate sustained EPS temperature limit of 160°F (71°C); dark finishes may exceed it in some climates. Consult Senergy Technical Services for project-specific suitability.

ASTERISK (*) Starred colors use organic pigments with lower lightfastness and greater fading risk. Inform the owner, architect and builder.

Standard Color Chart

Digital reference | Match and approve a physical sample before use.

				
3043 Pueblo LRV 75	3069 Sepia LRV 22	3032 Melon LRV 78	3070 Brunet LRV 25	3042 Nirvana* LRV 67
				
3071 Java LRV 28	3048 Lotus LRV 75	3072 Bulgur LRV 30	3054 Sonata LRV 76	433 Aztec Gold LRV 52
				
3057 Luna LRV 84	3065 Peanut LRV 52	3051 Windsong LRV 78	361 Champagne LRV 48	354 Stark White LRV 78
				
3105 Sandman LRV 54	330 Ultra White LRV 84	3106 Concord LRV 39	3058 Nightingale LRV 76	3107 Sage LRV 36
				
3096 Orchid* LRV 80	3108 Badger LRV 40	3092 New Frond* LRV 79	329 Putty Grey LRV 36	3095 Mint Tea* LRV 73
				
875 Grey Cloud LRV 28	606 Glacier* LRV 74	877 Slate Grey LRV 29	602 Crystal Blue* LRV 73	870 Storm Grey LRV 15
				
611 Robin Egg* LRV 60	880 Charcoal* LRV 8			

COLOR SELECTION Screens and printers show approximate colors. Choose a physical sample made by the applicator with the project tools, methods and materials before final selection.

DARK COLORS / EIFS Sika advises against colors below LRV 20 on EIFS containing expanded polystyrene (EPS). Its chart cites an approximate sustained EPS temperature limit of 160°F (71°C); dark finishes may exceed it in some climates. Consult Senergy Technical Services for project-specific suitability.

ASTERISK (*) Starred colors use organic pigments with lower lightfastness and greater fading risk. Inform the owner, architect and builder.